MONDOLUX

DOWNLIGHT

Benson Fixed



Product Code MD07FR

Technical Description

A proven performer

- A venerated all-rounder, the Benson is suitable for residential, commercial, retail and architectural applications
 The low-glare reflector and deep baffle ensure optimum visual comfort, whilst large cut-out enables practical installation
 Beam angle options: 25°, 35° and 60°
 Available in both Fixed and <u>Adjustable</u> versions
 Comes with IP40 protection

- If you require a customized version of this product, please contact us

Electrical Specifications	
System Power	9W, 13.5W
Input Voltage	240V
Control Type	ON/OFF, Phase-Cut, DALI, Casambi
System Efficacy (max.)	73lm/W
Power Factor	> 0.9
Photometric Info	
Luminaire Lumens	660lm, 970lm
CRI	CRI90
ССТ	2700K, 3000K, 4000K
Beam Angle	25°, 35°, 60°
Lumen Maintenance	> 50, 000hrs (L70 B10)
MacAdam Step	3 Step

Physical Characteristics

Installation Method	Fixed Recessed
Trim Finish	White, Black
IP Rating / IK Rating	IP40
Weight	1Kgs
Fitting Material	Aluminium

CE

RoHS


&





Polar Distribution Diagrams





Benson Fixed 25° 105 105 or 75 75 1000 1500 2000 45 15 30 cd/klm _____C0 - C180 n = 100% C90 - C270

Benson Fixed 35°

