

Stealth 2310 Recessed LINEAR LED



Product Code

ME06RE









Technical Description

A wide fit..

- Ideal for cabinet joinery in many types of applications
 Allows for less routing and more shelf to maintain the strength of the structure
 Paired with 180LED/m strip for dot free continuous illumination
 The recess lip hides any routing imperfections
 If you require a customised version of this product, please contact us

Electrical Specifications

| System Power | 10W, 14.4W, 15W, 19.2W |
|---------------|----------------------------|
| Input Voltage | 24V DC |
| Control Type | ON/OFF, DALI, Casambi, DMX |

Photometric Info

| Luminaire Lumens | 610lm, 785lm, 800lm, 1425lm, 2285lm |
|-------------------|---|
| CRI | CRI90 |
| ССТ | 2700K, 3000K, 3500K, 4000K, Tunable White(2600K-6500K) |
| Beam Angle | 110° |
| Lumen Maintenance | >50, 000hrs (L70B30) |
| MacAdam Step | 4 Step |


Physical Characteristics

| Installation Method | Fixed Recessed | |
|-----------------------|--|--|
| Trim Finish | White, Black, Silver | |
| IP Rating / IK Rating | IP20 | |
| Accessories | Linea COB 10W, Linea 14.4W, Linea-HE 14.4W, Linea COB Tunable White 15W, Linea-HE 19.2W | |
| Weight | 0.2Kgs | |
| Fitting Material | Aluminium | |



Polar Distribution Diagrams

Stealth 2310 110°





Stealth 2310 Recessed LINEAR LED

Product Accessories

| Item | Code | Description |
|-------------|----------|---|
| - | MAE53EC3 | Mondolux Accessories Extrusion End Cap Closed Stealth 2310 Recessed Silver |
| | MAE53EO3 | Mondolux Accessories Extrusion End Cap Open Stealth 2310 Recessed Silver |
| | MAE53EC1 | Mondolux Accessories Extrusion End Cap Closed Stealth 2310 Recessed White |
| | MAE53EO1 | Mondolux Accessories Extrusion End Cap Open Stealth 2310 Recessed White |
| | MAE53EC2 | Mondolux Accessories Extrusion End Cap Closed Stealth 2310 Recessed Black |
| ** | MAE53EO2 | Mondolux Accessories Extrusion End Cap Open Stealth 2310 Recessed Black |

Date created: 24/04/2024 mondolux.com.au