

Rho Mini Up/Down

OUTDOOR



Product Code

MO92



Technical Description

A minimalist's powerhouse

- Created exclusively for commercial outdoor applications, the Rho Mini Up/Down Wall Light boasts unmatched IP65 and IK06 ratings, standard CRI90, and a 5-year warranty*
- Designed with two non-adjustable beams of light, this lighting fixture is the perfect choice for both brightening surrounding areas and highlighting feature walls
- Cross beam Gen-2 lens
- UV stabilised matte finish in black
- Also available in Mini, Midi and Midi Up/Down options
- 3 step MacAdam binning
- If you require a customised version of this product, please [contact us](#)

***Please see Warranty Terms & Conditions for further information**

Electrical Specifications


System Power	12W
Input Voltage	240V
Control Type	Phase-Cut
System Efficacy (max.)	77lm/W
Power Factor	0.9

Photometric Info

Luminaire Lumens	920lm
CRI	CRI90
CCT	3000K
Beam Angle	2x14°, 2x32°, 2x48°
Lumen Maintenance	> 62, 850hrs (L70 B10)
MacAdam Step	3 Step


Physical Characteristics

Installation Method	Surface Mounted
Trim Finish	Black
IP Rating / IK Rating	IP65/ IK06
Fitting Material	Aluminium




Polar Distribution Diagrams

Rho Mini Up/Down 2x48°



Rho Mini Up/Down 2x32°



Rho Mini Up/Down 2x14°

