


Two thumbs up for low glare and uniform light distribution



- Low glare design: UGR<16
- Smooth distribution with soft cut-off
- High luminous efficacy: >89 lumens per watt
- Great thermal management with a forged aluminium heat sink
- Suitable for educational facilities, offices, corridors, shopping centres and any area where uniformity is key
- Ø145mm cutout

Product info

System Lumen Range	1850lm — 2500lm
System Power	20W, 28W
Forward Current	500mA, 700mA
System Efficacy (max.)	93lm/W
Input Voltage	240V
Body/Trim Colour	White
Installation Method	Fixed Recessed
Dimming Type	Non-Dimmable
Accessories	Without Accessory
Custom Dimming Type	Available on Request



Photometric info


Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K
Beam Angle	15°, 24°, 40°
Unified Glare Rating (UGR)	UGR<16
Custom Colour Temperature (CCT)	Available on Request

Packaging


Box Weight	0.9Kgs
Box Dimensions L x W x H mm	170mm x 170mm x 160mm
Boxes per Carton	16
Carton Weight	15.4Kgs
Carton Dimensions L x W x H mm	700mm x 355mm x 385mm

Polar distribution diagrams

Revenna 15°



Revenna 24°



Revenna 40°

