

Empire Plus II HIGHBAY



Product Code

MH32







Technical Description

Energy efficient industrial LED highbay lighting with quick ROI

The thin profile of the Empire Highbay makes it an ideal lighting solution for low ceilings in wet and dry locations such as warehouses, logistics centres, production workshops, storage facilities, commercial spaces, etc. Suspend this lightweight fitting with a chain (not included) for higher ceilings.

The patented heat sink thermal management ensures that the LED's heat is dispersed effectively - even in demanding environments - for a high lumen output and long product lifespan of 100,000H

If you require a customised version of this product, please contact us

Electrical Specifications

| System Power | 163W |
|------------------------|---------------------|
| Input Voltage | 240V |
| Control Type | ON/OFF, 0-10V/1-10V |
| System Efficacy (max.) | 158lm/W |

Photometric Info

| Luminaire Lumens | 25800lm |
|------------------|-----------|
| CRI | CRI70 |
| ССТ | 4000K |
| Beam Angle | 120°x120° |

Physical Characteristics

| Installation Method | Suspended |
|-----------------------|-----------|
| Trim Finish | Black |
| IP Rating / IK Rating | IP65 |
| Fitting Material | Aluminium |

Polar Distribution Diagrams

Empire Plus 120°

