




Energy efficient industrial LED highbay lighting with quick ROI

The thin profile of the Empire Highbay makes it an ideal lighting solution for low ceilings in wet and dry locations such as warehouses, logistics centres, production workshops, storage facilities, commercial spaces, etc. Suspend this lightweight fitting with a chain (not included) for higher ceilings.

The patented heat sink thermal management ensures that the LED's heat is dispersed effectively - even in demanding environments - for a high lumen output and long product lifespan of 100,000H.

Product info

System Lumen Range	32400lm
System Power	205W
System Efficacy	158lm/W
Input Voltage	240V
Body/Trim Colour	Black
Installation Method	Suspended
LED Brand	Lumileds/ Osram
IP Rating	IP65
Dimming Type	0-10V Dimmable, Non-Dimmable
Accessories	Without Accessory



Photometric info

Colour Rendering Index (CRI)	CRI70
Colour Temperature (CCT)	4000K
Beam Angle	120°x120°
Custom Colour Rendering Index (CRI)	Available on request
Custom Colour Temperature (CCT)	Available on request

Compliance and Features



Packaging

Box Weight	4.6Kgs
Boxes per Carton	0, 1

Empire Plus III

HIGHBAY | Product code MH33

MONDOLUX™
mondolux.com.au

Polar distribution diagrams

