

Albi Maxi Pro Adjustable

DOWNLIGHT



Product Code

MD31AR









Technical Description

Smart, striking design

- Part of the InfinitoPRO range of premium architectural downlights and spotlights
- The advanced PMMA hybrid lens, housed in a reflective enclosure, merges two optical designs to deliver a smooth, soft cut-off with precise directional control
- Engineered to reduce light spill and energy waste, providing excellent efficiency without compromising lighting quality or performance
 Ultra-low UGR: low glare and visual comfort in offices, architectural spaces, and public areas
- High fidelity with precise colour accuracy: enhanced rendering of rich, saturated colors and natural skin tones, with CRI97+ and 2-Step MacAdam as standard
- as standard

 Configure with Honeycomb Louvre, IP44 Glass, Frosted Diffuser, or Linear Diffuser accessories

 Albi Pro is available in Mini, Maxi, Fixed, Adjustable, Angular, Pinhole and Oval Pinhole versions

 If you require a customised version of this product, please contact us

Electrical Specifications

System Power	8W, 12W, 20W
Input Voltage	240V
Control Type	ON/OFF, Phase-Cut, DALI, Casambi
System Efficacy (max.)	89lm/W
Power Factor	0.9
Photometric Info	

Photometric Info

Luminaire Lumens	695lm, 1070lm, 1775lm
CRI	CRI97+
ССТ	2700K, 3000K, 4000K
Beam Angle	22°, 32°, 48°
Lumen Maintenance	>66000 hrs (L70 B10)
MacAdam Step	2 Step

Physical Characteristics

Installation Method	Adjustable Recessed
Trim Finish	White, Black
IP Rating / IK Rating	IP20
Weight	0.5Kgs
Maximum Tilt Angle	15°
Fitting Material	Aluminium

Albi Maxi Pro Adjustable 8W / 12W


Ø85mm

Albi Maxi Pro Adjustable 20W




153mm


Polar Distribution Diagrams



Albi Maxi Pro Adjustable 22°



Albi Maxi Pro Adjustable 32°





Albi Maxi Pro Adjustable

DOWNLIGHT

Product Accessories	
Without Accessory	Honeycomb Louvre
Line Diffuser	Frosted Diffuser
IP44 Diffuser	

Date created: 22/04/2025 mondolux.com.au