
MONDOLUX

 $(\bot$

SPOTLIGHT

Messina Midi





Product Code MS22

Technical Description

Small body, not-so-small output

- Introducing the Messina Midi Spotlight, a model of compact elegance combined with powerful performance
 Despite its small body, it delivers a robust output with an impressive luminous flux of up to 3450lm at CRI90, ensuring bright and accurate colour rendering
 - Cleverly engineered with a sleek and slim gearbox, showcasing the ingenuity of sophisticated design
 Beam spreads: Narrow (20°), Medium (30°), and Wide (60°)
 Wall washer version available upon request

- If you require a customised version of this product, please <u>contact us</u>

Electrical Specifications

System Power 20W, 28W, 36W Input Voltage 240V

Control Type System Efficacy (max.) 100lm/W

Photometric Info

| Luminaire Lumens | 1350lm, 2000lm, 1900lm, 2800lm, 2350lm, 3450lm |
|------------------|---|
| CRI | CRI90 |
| ССТ | 3000K, 3000K Vivid, 3500K, 4000K |
| Beam Angle | 20°, 30°, 60° |

Physical Characteristics

| Installation Method | 3-Circuit Track Mounted |
|------------------------|-------------------------|
| Trim Finish | White, Black |
| IP Rating / IK Rating | IP20 |
| Weight | 1.3Kgs |
| Maximum Tilt Angle | 90° |
| Maximum Rotation Angle | 350° |


CE


RoHS

&

Polar Distribution Diagrams

Messina Midi 59°





Messina Midi 20°

