

Exceptional architectural style



- Part of the Malo family
- Extended flexibility - max. 36° adjustable in both planes
- System lumen range from 675lm - 1830lm
- Tapered anti-glare snouts
- For any custom requirements, please contact us

Product info

System Lumen Range	675lm — 1830lm
System Power	7W, 13W, 18W
Forward Current	180mA, 350mA, 500mA
System Efficacy (max.)	102lm/W
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	CREE, Bridgelux
Dimming Type	Phase-Cut Dimmable, Wireless Dimmable (Casambi), Non-Dimmable, DALI Dimmable
Accessories	Without Accessory, Deep Baffle-Diamond, Deep Baffle-Frosted, Deep Baffle-IP44, Deep Baffle-Line, Diamond Diffuser, Frosted Diffuser, Honeycomb Louvre, IP44 Diffuser, Line Diffuser


Photometric info

Colour Rendering Index (CRI)	CRI90, CRI97+
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim To Warm
Beam Angle	15°, 30°, 50°

Compliance and Features




Malo Uno 7W




*allowed tolerance in mm

Malo Uno 13W



*allowed tolerance in mm

Malo Uno 18W




*allowed tolerance in mm

Packaging


Box Dimensions L x W x H mm	110 mm x 110 mm x 200 mm
Boxes per Carton	24
Carton Weight	12 KG
Carton Dimensions L x W x H mm	450 mm x 340 mm x 410 mm

Polar distribution diagrams

*Malo 7W/13W/18W 15°



*Malo 7W/13W/18W 30°



*Malo 7W/13W/18W 50°

