

Architectural flair



- Configure with Honeycomb Louvre, Line Diffuser, Diamond Diffuser or Frosted Diffuser accessories to further minimise glare and improve visual comfort
- Low glare design
- Suitable for residential and architectural lighting application
- Available in mini, maxi, round or oval pinhole versions
- For any custom requirements, please contact us

Product info

System Lumen Range	620lm — 1830lm
System Power	7W, 9W, 13W, 18W
Forward Current	180mA, 350mA, 500mA
System Efficacy (max.)	102lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	Fixed Recessed
LED Brand	CREE, Bridgelux
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable, Wireless Dimmable (Casambi), DALI Dimmable, Phase-Cut Dimmable
Accessories	Without Accessory, Deep Baffle-Diamond, Deep Baffle-Frosted, Deep Baffle-IP44, Deep Baffle-Line, Diamond Diffuser, Frosted Diffuser, Honeycomb Louvre, IP44 Diffuser, Line Diffuser


Photometric info

Colour Rendering Index (CRI)	CRI90, CRI97+
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim To Warm
Beam Angle	15°, 30°, 50°

Compliance and Features




Albi Maxi Fixed 7W




*allowed tolerance in mm

Albi Maxi Fixed 13W



*allowed tolerance in mm

Albi Maxi Fixed 18W



*allowed tolerance in mm

Albi Maxi Fixed

DOWNLIGHT | Product code MD31

Packaging

Box Dimensions L x W x H mm	110 mm x 110 mm x 200 mm
Boxes per Carton	0, 24
Carton Weight	12 KG
Carton Dimensions L x W x H mm	450 mm x 340 mm x 410 mm

Polar distribution diagrams

