

Combining form, function and technology



- Improved luminous efficiency with new Cross Beam Lens
- Deep recessed oval pinhole to minimise glare
- Standard SDCM: 3 steps, available in 2 steps on request
- Suitable for a several applications such as hospitality, retail, commercial & residential
- For any custom requirements, please **contact us**

Product info

System Lumen Range	675lm — 1830lm
System Power	7W, 13W, 18W
Forward Current	180mA, 350mA, 500mA
System Efficacy (max.)	102lm/W
Body/Trim Colour	White, Black
Installation Method	Adjustable Recessed
LED Brand	Bridgelux, CREE
Dimming Type	Wireless Dimmable (Casambi), Non-Dimmable, DALI Dimmable, Phase-Cut Dimmable
Accessories	Without Accessory, Deep Baffle-Diamond, Deep Baffle-Frosted, Deep Baffle-IP44, Deep Baffle-Line, Diamond Diffuser, Frosted Diffuser, Honeycomb Louvre, IP44 Diffuser, Line Diffuser


Photometric info

Colour Rendering Index (CRI)	CRI97+, CRI90
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim To Warm
Beam Angle	15°, 30°, 50°

Compliance and Features




Albi Oval Pinhole 7W




*allowed tolerance in mm

Albi Oval Pinhole 13W



*allowed tolerance in mm

Albi Oval Pinhole 18W



*allowed tolerance in mm

Albi Oval Pinhole

DOWNLIGHT | Product code MD33

MONDOLUX™
mondolux.com.au

Packaging

Box Dimensions L x W x H mm	110 mm x 110 mm x 200 mm
Boxes per Carton	24
Carton Weight	12 KG
Carton Dimensions L x W x H mm	450 mm x 340 mm x 410 mm

Polar distribution diagrams

