





## Large light for large walls

- High lumen outputs ranging from 1450lm to 3900lm
- Suitable for wall washing applications with high efficacies
- Tilt angle 0° - 90°
- Equipped with multiple wattage options 28W / 36W / 43W / 50W

### Product info

System Lumen Range	1450lm — 3900lm
System Power	28W, 36W, 43W, 50W
Forward Current	700mA, 900mA, 1050mA, 1200mA
System Efficacy Range	52lm/W to 78lm/W
Input Voltage	240V
Body/Trim Colour	White, Black
Installation Method	3-Circuit Track Mounted, Surface Mounted
LED Brand	Citizen
IP Rating	IP20
Diffuser	Clear
Dimming Type	Non-Dimmable, Phase-Cut Dimmable
Maximum Tilt Angle	90°
Maximum Rotation Angle	355°
Accessories	Without Accessory
Custom Dimming Type	Available on request



### Photometric info

Colour Rendering Index (CRI)	CRI90
Colour Temperature (CCT)	3000K, 3000K Vivid, 3500K, 3500K Vivid, 4000K, 4000K Vivid
Beam Angle	95°
Custom Colour Temperature (CCT)	Available on request
Revit Files	Please choose Beam Angle / Power within the Revit file

## Compliance and Features



## Packaging

Box Weight	2kg
Box Dimensions L x W x H mm	270 mm x 210 mm x 180 mm
Boxes per Carton	12
Carton Dimensions L x W x H mm	430 mm x 550 mm x 550 mm

## Polar distribution diagrams

