





Elegant design, made practical

- Great angle control - rotation 0° - 350° and tilt 0° - 60°
- Anti-glare honeycomb louvre accessory available
- 3-circuit track mount and surface mount installation options

Product info

| | |
|------------------------|--|
| System Lumen Range | 850lm |
| System Power | 11W |
| Forward Current | 500mA |
| System Efficacy | 77lm/W |
| Input Voltage | 240V |
| Body/Trim Colour | White, Black |
| Installation Method | 3-Circuit Track Mounted, Surface Mounted |
| LED Brand | Bridgelux |
| IP Rating | IP20 |
| Diffuser | Clear |
| Dimming Type | Phase-Cut Dimmable, Non-Dimmable |
| Maximum Tilt Angle | 60° |
| Maximum Rotation Angle | 350° |
| Accessories | Without Accessory, Honeycomb Louvre |
| Custom Dimming Type | Available on request |



Photometric info

| | |
|---------------------------------|----------------------|
| Colour Rendering Index (CRI) | CRI80 |
| Colour Temperature (CCT) | 3000K |
| Beam Angle | 18°, 35°, 48° |
| Custom Colour Temperature (CCT) | Available on request |

Compliance and Features



Packaging

| | |
|--------------------------------|--|
| Box Weight | 1kg |
| Box Dimensions L x W x H mm | 90 mm x 90 mm x 235 mm, 0 x 90 mm x 235 mm |
| Boxes per Carton | 20 |
| Carton Dimensions L x W x H mm | 470 mm x 295 mm x 460 mm |

Polar distribution diagrams

