

IP protection for extended usage



- IP54 rated downlight with compactly engineered design
- Beam angle options: 15°, 30°, 50°
- Dimmable Options: Phase-Cut, DALI, Casambi Wireless
- For any custom requirements, please **contact us**


Product info

System Lumen Range	675lm — 1830lm
System Power	7W, 13W, 18W
Forward Current	180mA, 350mA, 500mA
System Efficacy (max.)	102lm/W
Body/Trim Colour	White, Black
Installation Method	Fixed Recessed
LED Brand	CREE, Bridgelux
Dimming Type	Phase-Cut Dimmable, Wireless Dimmable (Casambi), Non-Dimmable, DALI Dimmable
Accessories	Without Accessory, Deep Baffle, Deep Baffle-Diamond, Deep Baffle-Frosted, Deep Baffle-Honeycomb, Deep Baffle-Line, Diamond Diffuser, Frosted Diffuser, Honeycomb Louvre, Line Diffuser

Photometric info


Colour Rendering Index (CRI)	CRI90, CRI97+
Colour Temperature (CCT)	2700K, 3000K, 4000K, Dim To Warm
Beam Angle	15°, 30°, 50°

Albi Mini IP Fixed 7W




*allowed tolerance in mm

Albi Mini IP Fixed 13W



*allowed tolerance in mm

Albi Mini IP Fixed 18W



*allowed tolerance in mm

Polar distribution diagrams

