

Genoa Mini

DC LOW VOLTAGE

Product Code

MV77



RoHS



Technical Description

Spread the light..

- Part of the Mondolux Pacto DC48V low-voltage range, and the smallest member of the Genoa family
- A discreet in-track linear luminaire that can be used to create continuous lines of light, with in-track installation to reduce visual bulk and maintain clean lines
- Wide beam angle of 110° for excellent uniformity, making it ideal for general area illumination
- Modular 48V click-in system for flexibility and easy installation
- Also available in [Midi](#) and [Maxi](#) sizes
- Non-dimmable and PWM DALI control options (Casambi Wireless Control available upon request)
- If you require a customised version of this product, please [contact us](#).

Electrical Specifications


| | |
|------------------------|--------------|
| System Power | 6W |
| Input Voltage | 48V DC |
| Control Type | ON/OFF, DALI |
| System Efficacy (max.) | 63lm/W |

Physical Characteristics

| | |
|-----------------------|-------------------|
| Installation Method | DC-Track Recessed |
| Trim Finish | White, Black |
| IP Rating / IK Rating | IP20 |
| Fitting Material | Aluminium |

Photometric Info

| | |
|------------------|--------------|
| Luminaire Lumens | 380lm |
| CRI | CRI80 |
| CCT | 3000K, 4000K |
| Beam Angle | 110° |



Polar Distribution Diagrams

Genoa Mini 110°

