MONDOLUX

DC LOW VOLTAGE

Genoa Midi



Product Code

MV78

Technical Description

Out of sight, front of mind

- Part of the Mondolux Pacto DC48V low-voltage range, and the middle member of the Genoa family
 A discrete in-track linear luminaire that can be used to create continuous lines of light, with in-track installation to reduce visual bulk and maintain clean lines
 Wide beam angle of 110° for excellent uniformity, making it ideal for general area illumination
 Modular 48V click-in system for flexibility and easy installation
 Also available in <u>Mini</u> and <u>Maxi</u> sizes
 Non-dimmable and PWM DALL control options (Casambi Wireless Control available upon request)
 If you cauring a curstemined warring of this product plages, control available upon request)

- If you require a customised version of this product, please $\underline{\mbox{ contact us}}$

Photometric Info

Luminaire Lumens

CRI


ССТ Beam Angle

| Electrical Specifications | |
|---------------------------|--------------|
| System Power | 11W |
| Input Voltage | 48V DC |
| Control Type | ON/OFF, DALI |
| System Efficacy (max.) | 71lm/W |

CRI80


110°

| Physical Characteristics | | |
|--------------------------|-------------------|--|
| Installation Method | DC-Track Recessed | |
| Trim Finish | White, Black | |
| IP Rating / IK Rating | IP20 | |
| Fitting Material | Aluminium | |



Polar Distribution Diagrams

Genoa Midi 110°



CE RoHS $\langle || \rangle$