

Pisa Midi DC LOW VOLTAGE



Product Code

MV36







Technical Description

The compact conqueror

- Part of the Mondolux Pacto DC48V low-voltage range, with our signature Cross-Beam Lens technology for increased efficacy

 The largest member of the Pisa family, with in-track installation to reduce visual bulk and maintain clean lines

 Multiple beam angle options available of 21°, 33°, and 42°

 Maximum tilt of 90° for excellent adjustability

 Configure with Honeycomb Louvre, Snoot, Oval Snoot, Line Diffuser or Frosted Diffuser accessories (available upon request) to further minimise glare, improve visual comfort and customise aesthetic appearance

 Modular 48V click-in system for flexibility and easy installation

 Also available in Nano Duc, Tiny and Misi sizes

- Also available in Nano Duo, Tiny Duo, Tiny Duo, Tiny and Mini sizes
 Non-dimmable and PWM DALI control options (Casambi Wireless Control available upon request)
 If you require a customised version of this product, please contact us

Electrical Specifications


System Power	20W
Input Voltage	48V DC
Control Type	ON/OFF, DALI
System Efficacy (max.)	63lm/W

Photometric Info

Luminaire Lumens	1260lm
CRI	CRI90
ССТ	3000K, 4000K
Beam Angle	21°, 33°, 42°
Lumen Maintenance	> 63, 200hrs (L70 B10)
MacAdam Step	3 Step

Physical Characteristics

Installation Method	DC-Track Recessed
Trim Finish	White, Black
IP Rating / IK Rating	IP20/IK05
Maximum Rotation Angle	90°
Fitting Material	Aluminium



Polar Distribution Diagrams

