# MONDOLUX

RoHS

CE

OUTDOOR

## Verne Midi Wall Washer





Product Code MO75

## **Technical Description**

- Captivating with durability...
- Outdoor uplight designed for commercial outdoor use
  Highly efficient, robust performance
  Exceptional IP67 and IK10 ratings with CRI90 as standard, low glare design and a 5-year warranty\*
  316 Stainless Steel trim with drive-over load rating of up to 2000Kg
  Marine grade powder coat available on request
- Variants include Tiny, Mini, Midi and Maxi sizes
- Local stock availability
   If you require a customised version of this product, please <u>contact us</u>
   \*Please see Warranty Terms & Conditions for further information.

### **Electrical Specifications**

System Power16WInput Voltage240VControl TypeON/OFFSystem Efficacy (max.)38/m/WPower Factor>0.9Photometric InfoCallCRICRI90CCT3000KBeam Angle55°x70°Lumen Maintenance>52,000hrs (L70 B10)MacAdam Step3 Step				
Control Type     ON/OFF       System Efficacy (max.)     38/m/W       Power Factor     > 0.9       Photometric Info        Luminaire Lumens     606/m       CRI     CRI90       CCT     3000K       Beam Angle     55°x70°       Lumen Maintenance     > 52, 000hrs (L70 B10)	System Power	16W		
System Efficacy (max.)     38lm/W       Power Factor     > 0.9       Photometric Info	Input Voltage	240V		
Power Factor     > 0.9       Photometric Info        Luminaire Lumens     606lm       CRI     CRI90       CCT     3000K       Beam Angle     55°×70°       Lumen Maintenance     > 52, 000hrs (L70 B10)	Control Type	ON/OFF		
Photometric Info       Luminaire Lumens     606Im       CRI     CRI90       CCT     3000K       Beam Angle     55°×70°       Lumen Maintenance     > 52, 000hrs (L70 B10)	System Efficacy (max.)	38lm/W		
Luminaire Lumens         606lm           CRI         CRI90           CCT         3000K           Beam Angle         55°×70°           Lumen Maintenance         >52, 000hrs (L70 B10)	Power Factor	> 0.9		
CRI         CRI90           CCT         3000K           Beam Angle         55°x70°           Lumen Maintenance         > 52, 000hrs (L70 B10)	Photometric Info			
CCT         3000K           Beam Angle         55°x70°           Lumen Maintenance         > 52, 000hrs (L70 B10)	Luminaire Lumens	606lm		
Beam Angle         55°×70°           Lumen Maintenance         > 52, 000hrs (L70 B10)	CRI	CRI90		
Lumen Maintenance > 52, 000hrs (L70 B10)	ССТ	3000K		
	Beam Angle	55°x70°		
MacAdam Step 3 Step	Lumen Maintenance	> 52, 000hrs (L70 B10)		
	MacAdam Step	3 Step		

Physical	Characteristics
----------	-----------------

	Installation Method	Fixed Recessed
	Trim Finish	316 Stainless Steel
	IP Rating / IK Rating	IP67/ IK10
	Weight	2.6Kgs
	Fitting Material	Aluminium & 316 Stainless Steel

Polar Distribution Diagrams

### Verne Midi Wall Washer 70° x 55° (Asym.)

